Conveyor 22®
Clean Electrical Engineering

Made in Sweden

Electric Transporter Clean Line 141

IP66

Patented electric shaker conveyor with smart maintenance-free technology.

Manufactured in stainless steel and anodized aluminium
Protection class IP66

Max distributed load	15 kg (33 Lb)
Max weight for tray	4 kg (8,8 Lb)
Stroke	20 mm (0,8”)
Feeding speed (mechanical adjustable)	4-8 m/min (13-26 ft/min)

The unit is delivered set to maximum speed. The speed may be reduced to increase the load capacity.

Sensor controlled shutdown warning	by M12 connector
Start/Stop function can be controlled	by M12 connector
Motor and overload protection	built-in
Noise level	60 dB (A)
Energy consumption	0,07 kW
Electricity	110-230 VAC, 50-60 Hz or 24 VDC
Protection class	IP66
Dimensions (LxWxH)	305x128x47 mm (12,0” x 5,0” x 1,85”)
Weight	3,7 kg (8,1 Lb)

WENNBERG INTERNATIONAL TRADERS LLC
8920 Kelly Lake Dr. Clarkston, Michigan, 48348 USA
Phone: +1 248-802-2604. Internet: wi@wennintl.com
Web: www.wennintl.com

© Conveyor 22 AB 2016-03